



50Hz电梯专用空调

50Hz ELEVATOR AIR CONDITIONER

型号 Model	TK-25Y	TKD-25Y	TK-25Y/Q	TKD-25Y/Q	TK-32Y	TKD-32Y	TK-32Y/Q	TKD-32Y/Q
额定制冷量 (W) Rated Cool Capacity (W)	2500	2500	2500	2500	3200	3200	3200	3200
额定制热量 (W) Rated Heat Capacity (W)	/	2200	/	2200	/	2200	/	2200
循环风量(高风/低风, m ³ /h) Air Flow (High/Low, m ³ /h)	430/360	430/360	430/360	430/360	530/430	530/430	530/430	530/430
制冷额定输入电流 (A) Rated Cool Input Current(A)	4.7	4.7	4.7	4.7	5.8	5.8	5.8	5.8
制冷额定输入功率 (W) Rated Cool Input Power (W)	1000	1000	1000	1000	1200	1200	1200	1200
制热额定输入电流 (A) Rated Heat Input Current(A)	/	10	/	10	/	10.3	/	10.3
制热额定输入功率 (W) Rated Input Power (W)	/	2200	/	2200	/	2255	/	2255
电源 Voltage/Frequency	220V~ 50Hz				220V~ 50Hz			
制冷剂 Refrigerant	R22	R22	R22	R22	R22	R22	R22	R22
噪声dB (A) Noise dB (A)	< 53	< 53	< 53	< 53	< 55	< 55	< 55	< 55
防水等级 Water Proof Level	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4
防触电保护类别 Insulated Voltage Grade	I类	I类	I类	I类	I类	I类	I类	I类
压缩机保护装置 Compressor Protection	过热保护 过电流保护 延迟启动保护 Overheat protection; Over current protection; Delay startup protection							
控制方式 Control Mode	程序控制 (自动)+红外线遥控 (手动) Program control (automatically) +infrared remote control (Manually)							
外形: 长*宽*高 (mm) Dimensions (L*W*H)mm	615*455*435		545*455*435		640*570*510		640*570*510	
质量 (kg) Weight(kg)	39.5	40	38.5	39	59	59.5	59	59.5
适用电梯 (kg) For Elevator(kg)	≤1350	≤1350	≤1350	≤1350	>1350	>1350	>1350	>1350
出风方式,回风方式 Air Out,Air return	下面出风, 下面回风 From Bottom ,To Bottom		前面出风, 前面回风 From Front ,To Front		两侧出风, 前面回风 From Two Sides ,To Front		前面出风, 前面回风 From Front ,To Front	



高效环保电梯专用空调(50Hz)

High Efficiency Environmental Elevator Air Conditioner(50Hz)

型号 Model	TK-26Y (R410A)	TKD-26Y (R410A)	TK-26Y/Q (R410A)	TKD-26Y/Q (R410A)	TK-35Y (R410A)	TKD-35Y (R410A)	TK-35Y/Q (R410A)	TKD-35Y/Q (R410A)
额定制冷量 (W) Rated Cool Capacity (W)	2600	2600	2600	2600	3500	3500	3500	3500
额定制热量 (W) Rated Heat Capacity (W)	/	2200	/	2200	/	2200	/	2200
循环风量(高风/低风, m ³ /h) Air Flow (High/Low, m ³ /h)	400 / 330	400 / 330	400 / 330	400 / 330	570 / 450	570 / 450	570 / 450	570 / 450
制冷额定输入电流 (A) Rated Cool Input Current(A)	4.3	4.3	4.3	4.3	5.8	5.8	5.8	5.8
制冷额定输入功率 (W) Rated Cool Input Power (W)	/	10.0	/	10.0	/	10.3	/	10.3
制热额定输入电流 (A) Rated Heat Input Current(A)	930	930	930	930	1250	1250	1250	1250
制热额定输入功率 (W) Rated Input Power (W)	/	2200	/	2200	/	2270	/	2270
电源 Voltage/Frequency	220-230V~50Hz				220-230V~50Hz			
制冷剂 Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
噪声dB (A) Noise dB (A)	<53	<53	<53	<53	<55	<55	<55	<55
防水等级 Water Proof Level	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4
防触电保护类别 Insulated Voltage Grade	I类	I类	I类	I类	I类	I类	I类	I类
压缩机保护装置 Compressor Protection	过热保护 过电流保护 延迟启动保护 Overheat protection; Over current protection; Delay startup protection							
控制方式 Control Mode	程序控制 (自动) +红外线遥控 (手动) Program control (automatically) +infrared remote control (Manually)							
外形: 长*宽*高 (mm) Dimensions (L*W*H)mm	615*455*435		545*455*435		640*570*510		640*570*510	
质量 (kg) Weight(kg)	40	40.5	39	39.5	57	57.5	57	57.5
适用电梯 (kg) For Elevator(kg)	≤1350	≤1350	≤1350	≤1350	>1350	>1350	>1350	>1350
出风方式,回风方式 Air Out,Air return	下面出风, 下面回风 From Bottom ,To Bottom		前面出风, 前面回风 From Front ,To Front		两侧出风, 前面回风 From Two Sides ,To Front		前面出风, 前面回风 From Front ,To Front	



TK(D)-25/26Y 型电梯空调
TK(D)-25/26Y Elevator
Air Conditioner

TK(D)-25/26Y/Q 型电梯空调
TK(D)-25/26Y/Q Elevator
Air Conditioner

TK(D)-32/35Y 型电梯空调
TK(D)-32/35Y Elevator
Air Conditioner

TK(D)-32/35Y/Q 型电梯空调
TK(D)-32/35Y/Q Elevator
Air Conditioner